

# 10 mm & 15 mm MINIATURE VALVES



All of the benefits of Clippard quality and reliability are now available in these 10 mm and 15 mm valves. Offered in both Normally-Open or Normally-Closed models, these 2-way and 3-way valves are perfect for small areas where compact electronically-controlled pneumatics are needed.

This series has a high strength, engineered light-weight glass filled nylon body, along with stainless steel, copper and Nitrile, making it suitable for a broad range of applications. With exceptional life and reliability this is the perfect sub-miniature valve for tomorrow's needs in a wide variety of industries.

## 10 mm Standard Series

Direct operating valves well-suited for single- or multiple-valve mounting in small spaces.

See pages 215 - 217



## 15 mm Standard Series

Direct operating valves well-suited for single- or multiple-valve mounting in small spaces.

See page 222 - 224



## 10 mm Latching Series

A short pulse of current shifts this valve which "latches" indefinitely; another pulse returns the valve.

See page 218



## 15 mm Latching Series

A short pulse of current shifts this valve which "latches" indefinitely; another pulse returns the valve.

See page 225



## 10 mm High Flow 2-Way Series

Specialty series for high flow applications.

See page 219



## 15 mm High Flow 2-Way Series

Specialty series for high flow applications.

See page 226



## 10 mm ISO 15218 Series

Conforms to ISO standard for mounting and port locations.

See page 220



All 10 mm and 15 mm valves are RoHS compliant.

**Valve Material:** Glass filled Nylon, Stainless Steel, Nitrile or FKM Elastomer

**Electrical:** The coil is constructed of copper wire and is insulated according to the class "F" standard. All circuitry and connections are protected from corrosion.

**Weight:** 10 mm Series: 0.4 oz.; 15 mm Series: 1.3 oz.

